Link/2500

PAYMENT SPECIALISTS

Your smart, sleek and simple payments solution



 Payment acceptance in your pocket! The ideal payment terminal for busy mobile merchants





The Link/2500 brings payment acceptance solution to any mobile business.



Pocket-sized, light weight and robust design, the Link/2500 is the perfect business acceptance point

Payments anywhere and anytime

• 4G, 3G, GPRS, Dual SIM, Bluetooth and WiFi

Raising the bar on security with PCI PTS compliancy

Designed for accessibility:

4

- Integrated speaker which could provide vocal assistance
- Real mechanical keypad with raised marking

ingenico

Π

\$12.00

Link/2500

2 3 F

Multiple alternative payment methods supported

 EMV Chip & PIN, contactless, magstripe or digital wallets

Optimized battery for a long business day on the go (up to 1200mAh)

Supported by Ingenico's suite of services

- Fleet management & security solutions
- Hardware services
- Professional services



			LINK/ 2500	LINK/ 2500 TOUCH	
Processor	Application & Crypto processor	• Cortex A5	~	~	
Memory	• Internal	 256 MB Flash, 128 MB RAM 128 MB Flash, 128 MB RAM 	✓	✓ Option	
os		• Telium TETRA	 	 	
SIM / SAM		• Up to 2	Option		
Card readers	• Magstripe • Smart card • Contactless	 ISO 1/2/3, 500K lifespan EMV Level 1, 50K lifespan EMV / iSO14443 	> > >	> > >	
Display	• Colour	 2.4" colour display, backlit, QVGA (240×320 pixels) 	~	~	
Keypad	• Mechanical	 20 keys, raised marking Backlighted keypad 	✓ N/A	✓ Option	
Audio	• Buzzer • Speaker		✓ Option	✓ Option	
Terminal connections	• USB Type C	• Host & Slave	~	 Image: A start of the start of	

			LINK/ 2500	LINK/ 2500 TOUCH
Terminal connectivity	• WAN	• 4G and/or 3G with fallback; Dual SIM	Option	Option
	• LAN	Bluetooth	Option	Option
	• LAN	• WiFi (Dual band)	Option Option	Option Option
	 Apple IAP Chip Multicom 	All connectivities in one single device	Option Option	Option Option
Terminal size	• L x W x H	• 129 × 70 × 17 mm (5.07 × 2.75 × 0.67)	~	N/A
		• 129 × 70 × 18 mm (5.07 × 2.75 × 0.70)	N/A	~
Power supply	• Terminal	• 5V 1A	Option	Option
Battery	• Li-ion	• 1200mAh (removable)	 Image: A start of the start of	~
Weight	• Full featured	• 155 g (5.46 oz)	 Image: A start of the start of	N/A
		• 167 g (5.89 oz)	N/A	~
Environment	 Charging Temperature 	• 0°C to +40°C (32°F to 104°F)	 	~
	 Operating Temperature 	 -10°C to +50°C (-14°F to 122°F) 	~	~
	 Storage Temperature 	 -20°C to +55°C (-4°F to 131°F) 	 	~
	 Operating Humidity 	• 85% non-condensing at +40°C (104°F)	~	~
Accessory	• Cable	• USB A to USB C: 1.5m	 	~
Security		PCI PTS 5.x online & offline certified	 Image: A start of the start of	~



UCP Inc. www.ucp-inc.com Tel.702-802-3504 Email. info@ucp-inc.com



7200 W Post Rd Suite 100, Las Vegas, NV, 89113