

Lane/3000

Enabling fast payments in lane





UCP Inc. www.ucp-inc.com

Tel.702-802-3504 Email. info@ucp-inc.com



Designed to manage thousands of transactions per day, the Lane/3000 is a cutting-edge retail PIN Pad, ideal for busy retailers.

TETRA

Optimized for payment

All payment methods accepted

Highest security:

- PCI PTS v6
- Optional PCI compliant privacy shield
- Detection of abnormal cable removal to alert and inhibit the terminal in the case of threat
- Anti-theft Kensington lock

Easy integration into semi-attended kiosks, with optimized dimension and adaptation plate

1 form factor but 2 versions:

- A modular version with high-end upgradable features, including a camera, WiFi or Bluetooth accessibility
- A non-modular version focuses exclusively on processing EMV payments for multilane checkouts

Designed for an intensive use in retail:

- Heavy duty magnetic stripe
- Smartcard readers optimized to boost transaction speeds
- Clear contactless zone

Supported by Ingenico's suite of services

- Fleet management & security solutions
- Hardware services
- Professional services





			MODULAR	NON- MODULAR
Processor	Applications & Crypto Processor	• Cortex A5	~	•
Memory	Internal External	• 256 MB Flash, 128 MB RAM • Micro SD up to 32 GB	Option	✓ N/A
os		Telium TETRA HTML5	•	~
SAM		• 1 • Up to 3	Option	Option
Card Reader(s)	Magstripe Second Magstripe (Dual Head) Smart Card Contactless	ISO1/2/3, 500K reads lifespan ISO1/2, 500K reads lifespan EMV Level 1, 500K reads lifespan EMV Level 1 3.0 spec compliant	Option ✓	N/A ✓
Camera		2M pixels (QR code library embedded)	Option	N/A
Display	• Colour	• 2.8" backlight, QVGA (320×240 pixels)	<	✓
Touchscreen	Capacitive	• Finger & stylus (1000K lifespan signature)	Option	Option
Keypad		15 keys, raised markings, backlit 4 function keys (non-touch version)	Option	Option
Audio	Buzzer Audio Jack Speaker	Stereo Mono	Option Option	Option Option

			MODULAR	NON- MODULA
Terminal Connectivity	• Wired • Wireless	Ethernet 10/100 base T WIFI and Bluetooth	Option	V N/A
Terminal Connections	• USB	• USB Host	✓	✓
		USB Slave	~	~
	Serial Powered USB	• 1 RS232	~	~
	Powered USB Powered RS 232	• 12 V (USB retail)	~	~
	Powered R3 232 Powered Ethernet	• 12 V	✓	~
	Towered Ethernet	PoE 802.3af compliant	Option	N/A
	External Power Supply		Option	Option
Stand Mounting		Universal Payment Mount	✓	•
Terminal Size		• 83 × 180 × 43 mm (3.26×7.08×1.69")	✓	•
Weight		• 254 g (8.89oz)	✓	▽
Environment	Operating temperature	• 0 to +50°C (32°F to 122°F)	✓	<u>~</u>
	Storage temperature	• -20 to +70°C (-4°F to 131°F)	~	~
	Relative humidity	• 85% HR at +40°C (104°F)	~	~
Accessories	Privacy shield (factory mouted)	PCI compliant	✓	<u> </u>
	Stylus kit		Option	Option
Security	• PCI PTS	PCI PTS 6.x and 5.x certified	✓	~
	Anti-removal	Active connector removal	✓	~
	Anti-theft	Kensington lock receptacles	~	~
		Secure mounts available	Option	Option



UCP Inc. www.ucp-inc.com Tel.702-802-3504 Email. info@ucp-inc.com

