

## 4.5" MOBILE POS/ PAYMENT TERMINAL

The APT-40Mini is a pocket-sized payment processing powerhouse packed with features and value. Its compact footprint is the ideal choice for merchants seeking a lightweight, highly mobile and secure payments solution. It has all the features for exceptional performance in retail, hospitality, transportation, delivery and many other verticals. This innovative payment terminal is powered by the Android OS, allowing download and installation of certified Apps for increased functionality on-demand. No matter what your mobile payments needs are, chances are the TEAMSable APT-40Mini has everything you need to "swipe", "dip", or "tap" cards successfully to improve your business' bottom line.

## APT-40Mini Mobile Terminal Features at a Glance:

- Durable 4.5" PCAP Touchscreen
- Responsive 1.2GHz Quad Core CPU
- Snappy Performance 1G DDR3
- Ample 8GB Flash Storage Capacity
- WiFi, Bluetooth, Cellular & GPS Connectivity Options

## **FEATURES**



**Integrated MSR** 



**Integrated EMV Reader** 





**Compact Footprint Design** 

**Built-in NFC & Camera** 



UCP Inc. www.ucp-inc.com Tel.702-802-3504 Email. info@ucp-inc.com

7200 W Post Rd Suite 100, Las Vegas, NV, 89113

## **Certification and Software**

- Supports Major Payment Processors
- PCI 4.X & EMV L3 Certified
- Payment APK Available
- Windows API Available
- Android SDK Available









Supports Major Processors

Windows **API Availbale** 

Android **SDK Availbale** 



EMV & PCI

	APT-4	0Mini	
CPU and Memory		Ports	
Operating System	Android 5.1	Micro USB	USB OTG x 1
CPU	QuadCore 1.2Hz	SIM Card	1 Slot
Memory	1GB DDR3	PSAM Card	1 Slot
Storage	8GB eMMC	Speaker	Support
TF Socket	Support up to 32GB	Microphone	Support
Display		Headset	3.5mm Jack
Panel	4.5" IPS 854 x 480	Power	
Touch	5 Point Capacitive	Battery	3.7V/3000 mAh Lithium
Wireless Connectivity		Power Adapter	Input 100-240V; Output 5V/2A
WIFI	IEEE 802.11b/g/n, WLAN 2.4GHz+5GHz	Camera	
Bluetooth	BLE 4.0 Dual Mode, V4.0+EDR	Rear Camera	5M Pixel, AF
GPS	Optional	Scanner	Support to scan 1D, 2D barcode (QR Code)
Cellular Module	3G and 4G	Physical Dimension	
Card Reader		Size	132x69x22mm
Magnetic Reader	Track 1/2/3, ISO7810&7811, Bi-Directional, PCI 4.X and EMV Co.	Weight	227g
IC Chip	ISO 7816, Encrypted head, PCI 4.X and EMV Co.	Environment	
NFC	ISO/ IEC 14443, Type A&B	Operating Temperature	-20°C - 60°C
		Storage Temperature	-30°C - 80°C